


USB CURVA 45°




CARACTERÍSTICAS

COR	Preto
MATÉRIA PRIMA	PP-MD
TIPO DE LIGAÇÃO	Push-fit
SÉRIE	16
NORMAS	EN 1451-1 ISO 7671 HR 3.43
SISTEMAS COMPATÍVEIS	ULTRA SILENT

REF	Ø	L	Z1	Z2	
	(mm)				(un)
HL7070000470	32	53,0	8	13,0	40
HL7070010470	40	58,5	11	17,0	40
HL7070020470	50	64,0	13	19,0	40
HL7070030470	75	74,5	18	24,0	20
HL7070090470	90	81,0	21	27,5	20
HL7070040470	110	94,0	25	33,5	20
HL7070050470	125	104,0	29	38,0	10
HL7070060470	160	116,0	36	44,0	5
HL7070080470	200	148,0	49	63,0	3

USB CURVA 67,5°



CARACTERÍSTICAS

COR	Preto
MATÉRIA PRIMA	PP-MD
TIPO DE LIGAÇÃO	Push-fit
SÉRIE	16
NORMAS	EN 1451-1 ISO 7671 HR 3.43
SISTEMAS COMPATÍVEIS	ULTRA SILENT

REF	Ø	L	Z1	Z2	
	(mm)				(un)
HL7070000670 ⁽⁷⁾	32	58,0	13	18	50
HL7070010670 ⁽⁷⁾	40	65,5	18	24	40
HL7070020670 ⁽⁷⁾	50	72,5	21	27	40
HL7070030470 ⁽⁷⁾	75	85,5	29	35	20
HL7070090670 ⁽⁷⁾	90	94,0	34	40	20
HL7070040670 ⁽⁷⁾	110	110,0	44	48	20

⁽⁷⁾ Disponível sob consulta.