


USR REDUÇÃO




CARACTERÍSTICAS

COR	Preto
MATÉRIA PRIMA	PP-MD
TIPO DE LIGAÇÃO	Push-fit
SÉRIE	16
NORMAS	EN 1451-1 ISO 7671 HR 3.43
SISTEMAS COMPATÍVEIS	ULTRA SILENT

REF	Ø ₁	Ø ₂	L	Z	t	
	(mm)					(un)
HL7072110070	40	32	48	14	42	30
HL7072120070	50	32	65	15	42	30
HL7072121070	50	40	64	15	42	30
HL7072132070	75	50	85	26	47	20
HL7072191070	90	40	93	35	47	32
HL7072192070	90	50	97	34	47	20
HL7072193070	90	75	86	24	51,5	20
HL7072141070	110	40	122,5	51	43	20
HL7072142070	110	50	118	46	47	20
HL7072143070	110	75	106	34	52	20
HL7072149070	110	90	101	29	55	20
HL7072154070	125	110	106	29	64	10
HL7072164070	160	110	137	84	64	10
HL7072165070	160	125	140	74	55	16
HL7072186070	200	160	153	54	80	6

USR REDUÇÃO CURTA



CARACTERÍSTICAS

COR	Preto
MATÉRIA PRIMA	PP-MD
TIPO DE LIGAÇÃO	Push-fit
SÉRIE	16
NORMAS	EN 1451-1 ISO 7671 HR 3.43
SISTEMAS COMPATÍVEIS	ULTRA SILENT

REF	Ø ₁	Ø ₂	e	L	L1	
	(mm)					(un)
HL7072392070 ⁽⁷⁾	50	90	16,5	85,8	61,0	20
HL7072342070 ⁽⁷⁾	50	110	26,1	94,5	69,0	20
HL7072343070 ⁽⁷⁾	75	110	13,6	95,6	69,0	20
HL7072349070 ⁽⁷⁾	90	110	6,1	92,0	69,0	20

⁽⁷⁾ Disponível sob consulta.