


USMM UNIÃO DUPLA




CARACTERÍSTICAS

COR	Preto
MATÉRIA PRIMA	PP-MD
TIPO DE LIGAÇÃO	Push-fit
SÉRIE	16
NORMAS	EN 1451-1 ISO 7671 HR 3.43
SISTEMAS COMPATÍVEIS	ULTRA SILENT

REF	Ø	L	Z	t	
	(mm)				(un)
HL7071700270 ⁽²⁾	32	56,6	2,0	14,3	50
HL7071710270	40	60,0	2,0	14,0	40
HL7071720275	50	64,0	4,0	16,0	20
HL7071730275	75	73,0	6,0	16,4	20
HL7071790270	90	85,0	1,4	14,0	20
HL7071740275	110	97,0	9,0	17,0	20
HL7071750275	125	118,6	10,4	17,0	10
HL7071760275	160	119,0	10,6	23,0	12
HL7071780275	200	135,0	12,0	28,5	2

⁽²⁾ Limitado ao stock existente.

USU UNIÃO SIMPLES



CARACTERÍSTICAS

COR	Preto
MATÉRIA PRIMA	PP-MD
TIPO DE LIGAÇÃO	Push-fit
SÉRIE	16
NORMAS	EN 1451-1 ISO 7671 HR 3.43
SISTEMAS COMPATÍVEIS	ULTRA SILENT

REF	Ø	L	t	
	(mm)			(un)
HL7071700070	32	56,6	14,3	50
HL7071710070	40	60,0	14,0	30
HL7071720070	50	68,0	14,0	20
HL7071730070	75	77,0	14,0	20
HL7071790070	90	85,0	14,0	20
HL7071740070	110	97,0	17,0	20
HL7071750070	125	118,6	16,8	10
HL7071760070	160	131,0	17,0	12
HL7071780070	200	192,2	28,3	2